



MATERIAL SAFETY DATA SHEET

Product Name **BREAK UP**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name DIVERSEY AUSTRALIA PTY. LIMITED
Address 29 Chifley St, Smithfield, NSW, AUSTRALIA, 2164
Telephone (02) 9757 0300
Fax (02) 9725 5767
Emergency 1800 033 111 (24 hrs)
Email aucustserv@diversey.com
Web Site <http://www.diversey.com>
Synonym(s) 739253 BREAK UP 4X5L • HH15399 BREAK UP 25L
Use(s) CLEANING AGENT • DEGREASER • DEGREASING AGENT
SDS Date 08 Mar 2010

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R36/38 Irritating to eyes and skin.

SAFETY PHRASES

S2 Keep out of reach of children.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
ETHYLENE GLYCOL MONOBUTYL ETHER	C6-H14-O2	111-76-2	<10%
SODIUM METASILICATE ANHYDROUS	Na2-Si-O3	6834-92-0	<10%
ALKALINE SALT(S)	Not Available	Not Available	<10%
BUILDER	Not Available	Not Available	<10%
CHELATING AGENT(S)	Not Available	Not Available	<10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	remainder

4. FIRST AID MEASURES

Eye	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
Advice to Doctor	Treat symptomatically
First Aid Facilities	Eye wash facilities and safety shower should be available.

5. FIRE FIGHTING MEASURES

Flammability	Non flammable. May evolve toxic gases if strongly heated.
Fire and Explosion	Treat as per requirements for Surrounding Fires: Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	Use personal protective equipment. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. CAUTION: Spill site may be slippery.
-----------------	---


7. STORAGE AND HANDLING

Storage	Store in a cool, dry, well ventilated area, removed from oxidising agents, acids and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	2-Butoxyethanol (EGBE)	ASCC (AUS)	20	96.9	50	242

Biological Limits	No biological limit allocated.
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.
PPE	Wear splash-proof goggles, rubber or PVC gloves and coveralls. When using large quantities or where heavy contamination is likely, wear: a PVC apron, rubber boots and a faceshield.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	CLEAR PALE YELLOW LIQUID	Solubility (Water)	SOLUBLE
Odour	CHARACTERISTIC ODOUR	Specific Gravity	1.11
pH	13.2 - 13.5	% Volatiles	> 60 % (Water)

Product Name **BREAK UP**

Vapour Pressure	18 mm Hg @ 20°C	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	100°C	Upper Explosion Limit	NOT RELEVANT
Melting Point	< 0°C	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	AS FOR WATER		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), metals, heat and ignition sources.
Decomposition	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	This product has the potential to cause adverse health effects. Use safe work practices to avoid eye or skin contact and inhalation. Over exposure may result in corrosive tissue damage.
Eye	Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Inhalation	Over exposure may result in irritation of the nose and throat, coughing, nausea and inflammation with breathing difficulties. Due to the low vapour pressure, an inhalation hazard is not anticipated with normal use.
Skin	Contact may result in irritation, redness, pain, rash, dermatitis and possible burns.
Ingestion	Ingestion may result in ulceration and burns to the mouth and throat, nausea, vomiting, abdominal pain and diarrhoea.
Toxicity Data	ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2) LC50 (Inhalation): 700 ppm (mouse) LD50 (Ingestion): 300 mg/kg (rabbit) LD50 (Skin): 230 mg/kg (guinea pig) TCLo (Inhalation): 100 ppm (human) TDLo (Ingestion): 7813 uL/kg (woman) SODIUM METASILICATE ANHYDROUS (6834-92-0) LD50 (Ingestion): 770 mg/kg (mouse) LDLo (Ingestion): 250 mg/kg (dog) LDLo (Intraperitoneal): 200 mg/kg (guinea pig) TDLo (Ingestion): 15 g/kg (rat)

12. ECOLOGICAL INFORMATION

Environment	WATER: If released to waterways, alkaline products may change the pH of the waterway. Fish will die if the pH reaches 10-11 (goldfish 10.9, bluegill 10.5). SOIL: May leach to groundwater with toxic effects on aquatic life as above. ATMOSPHERE: Not expected to reside in the atmosphere. Drops or particles released to atmosphere should be removed by gravity and/or be rained out.
--------------------	--

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Neutralise with dilute acid (eg. 3 mol/L hydrochloric acid) or similar. For small amounts absorb with sand or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport	Not classified as Dangerous Good by the criteria of the Australian Dangerous Goods Code (ADG Code) for the transport by Road and Rail, 6th edition.
------------------	---

Product Name **BREAK UP**

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated				
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794

Product Name **BREAK UP**

Email: info@rmt.com.au

Web: www.rmt.com.au

SDS Date: 08 Mar 2010

End of Report